

Datasheet

Art.No. 96.030.0253.0

Distributor RST20i3V 3P1 V GL

Distribution block RST20i3, 3 pole, 1 input, 3 outputs, without mounting option, 250V/20A, color of coding: light gray



Art.No.	96.030.0253.0
EAN	4015573734753
Order unit	1 pieces

Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE

Model

Number of inputs	1
Number of outputs	3
Type of fastening	No
Degree of protection (IP)	IP66/68 (3m;2h) /IP69K
Type of distributor	Distribution terminal block

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	55.5 mm
Width	69.6 mm
Height	31.3 mm

Classification

ECLASS 8.1	27440603: Compact distributor for plug-in building installation
ETIM 5.0	EC002567: Compact distributor for plug-in building installation
ETIM 4.0	EC002567: Compact distributor for plug-in building installation



Drawings

